

PAT-NO: JP404069236A

DOCUMENT-IDENTIFIER: JP 04069236 A

TITLE: METAL-DEPOSITED POLYESTER FILM

PUBN-DATE: March 4, 1992

INVENTOR-INFORMATION:

NAME

SEKI, SHIGEMI

NAKAHARA, KATSUJI

MATSUURA, KAZUO

ASSIGNEE-INFORMATION:

NAME

TORAY IND INC

COUNTRY

N/A

APPL-NO: JP02183427

APPL-DATE: July 11, 1990

INT-CL (IPC): B32B015/08, B29C055/02 , B32B007/02 , B32B007/04 ,
B32B027/40
, C08J007/04 , C23C014/20

US-CL-CURRENT: 428/458, 428/938

ABSTRACT:

PURPOSE: To make processability on postprocessing good and to provide enough durability under a high moisture atmosphere by forming a metal deposition layer on a polyester film the surface of which is modified with a specified reactive urethane.

CONSTITUTION: A surface-modified layer wherein an aq. self-emulsifying heat-reactive urethane is a main ingredient with a solvent swelling ratio of 50 % or smaller and with a water swelling ratio of 80 % or smaller is provided on at least one face of a polyester film and a metal-deposited layer is furthermore provided on the surface-modified layer to obtain a metal-deposited polyester film. It is pref. that the reactive urethane contains hydroxyl groups as an active hydrogen atom supporting the characteristics best and it is especially pref. that a polyester and a polyether ester have two or more hydroxyl groups. The metal-deposited layer constituting the film is a layer formed by adhering a metal or an alloy contg. the metal on a surface-modified layer of the base polyester film by means of a well known vacuum deposition method such as vapor deposition, sputtering and ion plating.

COPYRIGHT: (C)1992,JPO&Japio